

PERFORMANCE DATA SHEET NEMA PREMIUM NR CAN NEMA 12 - 12

Catalogue #: **MPP-64**

HP	kW	Voltage	S.F. @ 60Hz	EFF.	P.F.	Frame	Design	L.R. Amps
50	37,30	575	1,15	92,4%	0,76	404T	B	348

60 Hz								
FLA							Code	F.L. RPM
208	230	416	460	480	575	600		
/	/	/	/	/	53,2	/	G	885

50 Hz								
FLA			S.F. @ 50Hz		Efficiency	Power Factor	Code	F.L. RPM
190	380	415						
/	/	/	/		/	/	/	/


Wgt. Lbs	PH	Duty	Insul. Class	Amb.	Elevation	Temp. Rise° C
902	3	Cont.	F	40°C	1000M (3300 Ft)	< 80

% Efficiency		% Power Factor		Torque			
Full Load:	92,4%	Full Load:	0,76	Full Load Ft/Lbs	296,7	Winding Resist. Ω	Safe Cold Start (Secs)
3/4 Load:	92,4%	3/4 Load:	0,69	Locked Rotor %	200		
1/2 Load:	91,5%	1/2 Load:	0,60	Break Down %	240		

Rotor Inertia Wk2 Lb-Ft2	Max Load Inertia Wk2 Lb-Ft2	Shaft Material	Frame Material	DE Bracket Type	ODE Bracket Type	Enclosure	NEMA Rating	Lead Wire Size
23,73	1120	Standard	Cast Iron	Standard	Standard	TEFC	IP55	7AWG

Ball Bearings		Grease	Mount Type	Orientation	Paint	Sound Pressure @ 3FT	Sound Power
DE	ODE						
NU318	6314						
		Mobil PolyrexEm	Rigid	Horizontal	Green	72	84

Inverter Duty. Motor meets MG1 parts 31.4.4.2	Constant Torque Range	Variable Torque Range	Constant HP RPM
	10:1	20:1	1350




Date: 2020-02-27
 Customer: _____
 Contact: _____
 Submittee: J.C. Lavallée


Catalogue #: MPP-64

NEMA PREMIUM NR CAN NEMA 12 - 12										
HP	VAC	RPM	Enclosure	Frame	Frequency	Design	Poles	LR Code Letter	Insulation Class	Temp. Rise °C
50	575	885	TEFC	404T	60	B	8	G	F	< 80
	0Hz	6Hz	15Hz	30Hz	45Hz	60Hz	75Hz	90Hz	105Hz	120Hz
Amps	53,2	53,2	53,2	53,2	53,2	53,2	53,2	53,2	53,2	53,2
RPM	0	88,5	221,25	442,5	663,75	885	1106,25	1327,5	1548,75	1770
Torq ft.lb	237,38	296,72	296,72	296,72	296,72	296,72	237,38	197,82	169,56	148,36
Peak Tq ft.lb	326,40	652,79	652,79	652,79	652,79	652,79	522,23	435,19	373,02	326,40
HP	0	5,0	12,5	25,0	37,5	50,0	50,0	50,0	50,0	50,0
	Locked Rotor	Pull-Up	Breakdown	Rated Load	Idle	Duty	S. F.	Ambient	Elevation	dBA @ 1M
Speed (RPM)	0,0	378	720	885	900	Continuous	1,15	40°C	3300 ft	72
Current (Amps)	348,0	295,8	207,1	53,2	20,6	VFD Rating: Meets MG1 parts 31.4.4.2				
Torque (ft.-lbs)	593,4	445,1	712,1	296,7	0,0	C.T.	10:1	V.T.	20:1	

Motor Speed Data



Motor Torque Capability vs RPM




Date: 2020-02-27
 Customer:
 Contact:
 Submittee: J.C. Lavallée

Catalogue #: MPP-64

NEMA PREMIUM NR CAN NEMA 12 - 12										
HP	VAC	RPM	Enclosure	Frame	Frequency	Design	Poles	LR Code Letter	Insulation Class	Temp. Rise °C
50	575	885	TEFC	404T	60	B	8	G	F	< 80
Load %	0%	25%	50%	75%	100%	125%	150%			
Amps	20,59	22,88	32,03	42,88	53,20	64,96	76,00			
Torq ft/lbs	0	73,25	147,11	221,60	296,72	372,48	448,89			
RPM	0	896,25	892,5	888,75	885	881,25	877,5			
Eff	0	80,41	91,50	92,40	92,40	92,40	92,40			
PF	0	50,9	60	69	76	78	80			
Locked Rotor	Pull-Up	Breakdown	Rated Load	Idle	Duty	S. F.	Ambient	Elevation	dBA @ 1M	
Speed (RPM)	0	378	720	885	900	Continuous	1,15	40°C	3300 ft	72
Current (Amps)	348	295,8	207,1	53,2	20,5884	VFD Rating: Meets MG1 parts 31.4.4.2				
Torque (ft-lbs)	593,45	445,08	712,14	296,72	0,0	C.T.	10:1	V.T.	20:1	

Motor Speed Data



Motor Load Data

