



# Agricultural Fan Motors

## FARM DUTY PSC MOTOR

TEAO TOTALLY ENCLOSED AIR OVER DESIGN

VARIABLE SPEEDS | VARIABLE SPEED CONTROLLED 1 PHASE INPUT

Features:

- Ball Bearings
- Continuous Duty
- Extended Thru-Bolts
- Automatic Reset Thermal Overload
- Full Gasketed
- 1/2" x 2-1/2" Long Shaft with Two Flats, 90 Degree Apart
- UL reconized and CSA Certified

MaxMotion



HP	RPM	VOLTS	FRAME	CAT NO	F.L. AMPS	WT (LBS)	C DIMENSION (INCH)
1/3	1625	115/230	48YZ	MVS-134SB	3.8/1.9	22.15	11.81
1/2	1625	115/230	48YZ	MVS-124SB	5.4/2.7	24.4	11.81

## SPECIAL APPLICATION FARM DIRECT DRIVE POULTRY FAN

Features:

- Continuous Duty
- PSC Models Include Capacitor Mounted With Cover
- Clockwise Drive End Rotation
- Automatic Reset Thermal Overload Protection
- Studs For Mounting Fan Guard
- Terminal Board With Side Conduit Plug



HP	RPM	VOLTS	FRAME	CAT NO	F.L. AMPS	WT (LBS)	C DIMENSION (INCH)
1/4	1725	115/230	48Y	1255	2.5/1.3	16	12.9
1/3	1700	115/230	48Z	FD13AA2P4Z9	3.8/1.9	19	10.4
1/2	1140	115/230	48Y	1195	5.8/2.8	19	12.9
	1700	115/230	48Z	1850	5.0/2.5	23	10.9



# Agricultural Fan Motors

## FARM DUTY PSC MOTOR

TEAO TOTALLY ENCLOSED AIR OVER DESIGN  
VARIABLE SPEEDS | THRU BOLT



Features:

- Ball bearings
- Continuous duty
- Extended thru-bolts
- Automatic reset thermal protector
- Fully gasketed
- 48/56 Frame mounting holes
- 1/2" dia. x 2-1/2" long shaft with two flats, 90° apart
- UL recognized and CSA certified



HP	RPM	VOLTS	FRAME	CAT NO	F.L. AMPS	WT (LBS)	C DIMENSION (INCH)
1/4	1625	115/230	48YZ	X024	3.2/1.6	18	10.09
	1075	115/230	48YZ	X027	3.2/1.6	15	10.09
	1625	115/230	48YZ	X030	3.6/1.8	20	11.06
1/3	1625	115/230	48YZ	X025	4.4/2.2	18	10.09
	1075	115/230	48YZ	X028	4.2/2.1	21	10.84
	1625	115/230	48YZ	X031	3.8/1.9	23	11.81
	1625	115/230	48YZ	X031SB	3.8/1.9	18	11.81
1/2	1625	115/230	48YZ	X026	6.0/3.0	22	10.84
	1075	115/230	48YZ	X029	6.4/3.2	22	10.84
	1625	115/230	48YZ	X032	5.4/2.7	24	11.81
	1625	115/230	48YZ	X032SB	5.4/2.7	22	11.81



## EXHAUST BLOWER

CFM	RPM	VOLTS	FRAME	CAT NO	AMPS	WT (LBS)	BODY LENGTH
155	2480	115	3.3	R7-RB155	0.75	13	5.67
165	3550	115	3.3	R7-RB165	0.65	7	7.16