



Version: 2WTI		Revised: 26-01-2023		<b>HP</b>	<b>RPM</b>	<b>FRAME</b>	<b>ENCLOSURE</b>	<b>JMPP/JMQP-16</b>							
Customer is responsible in determining that MEP product will fit/perform suitably in the intended application								3	3600	182JM	TEFC				
<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>2E</b>	<b>2F</b>	<b>G</b>	<b>H</b>	<b>J</b>	<b>O</b>	<b>P</b>	<b>R</b>			
9.50	7.30	18.48	4.50	3.75	7.50	4.50	0.60	0.41	2.00	9.10	8.70	0.771-0.756			
<b>S</b>	<b>T</b>	<b>U</b>	<b>AA</b>	<b>AB</b>	<b>AH</b>	<b>AJ</b>	<b>AK</b>	<b>BA</b>	<b>BB</b>	<b>BC</b>	<b>BD</b>	<b>EL</b>	<b>EM</b>		
0.190-0.188	1.60	0.8740-0.8745	0.75	7.50	4.25	5.875	4.500-4.497	3.50	0.156-0.125	0.12	6.62	1.250-1.248	1.00-0.9995		
<b>EN</b>	<b>EP</b>	<b>EQ</b>	<b>ER</b>	<b>ES</b>	<b>ET</b>										
3/8-16	1.57	0.640-0.610	4.281-4.219	1.65	2.890-2.860										