



| | | | | | | | | | | | | | | | | |
|---|------|---------------------|-------------|------|-------------|-------|-------------|--------------|-------------|-------|------|-------------|---------------|--|--|--|
| Version: 1WTI | | Revised: 01-04-2020 | | HP | RPM | FRAME | ENCLOSURE | JPPP-JPQP-22 | | | | | | | | |
| Customer is responsible in determining that MEP product will fit/perform suitably in the intended application | | | | | | | | 5 | 1800 | 184JP | TEFC | | | | | |
| A | B | C | D | E | 2E | 2F1 | 2F2 | G | H | J | O | P | R | | | |
| 9.50 | 8.30 | 22.55 | 4.50 | 3.75 | 7.50 | 4.50 | 5.50 | 0.60 | 0.41 | 2.00 | 9.10 | 8.70 | 0.771-0.756 | | | |
| S | T | U | AA | AB | AH | AJ | AK | BA | BB | BC | BD | EL | EM | | | |
| 0.190-0.188 | 1.60 | 0.8740-0.8745 | 0.75 | 7.50 | 7.312 | 5.875 | 4.500-4.497 | 3.50 | 0.156-0.125 | 0.12 | 6.62 | 1.250-1.248 | 1.0000-0.9995 | | | |
| EN | EP | EQ | ER | ES | ET | | | | | | | | | | | |
| 3/8-16 | 1.57 | 1.578-1.548 | 7.343-7.281 | 1.65 | 5.952-5.922 | | | | | | | | | | | |