



1-11.5 NPT
SIZE CONDUIT

Ø.44±.05
4 HOLES

SHAFT KEYWAY VIEW

FRAME	TYPE	ENCL	VOLTAGE	HP	POLE	PH	HZ	RPM	THERMAL PROTECTION
215TZ	TMQ	TEFC	230	5	4	1	60	1725	MANUAL RESET

- NOTES:
- .25 X .25 X 2.50 KEY SHIPPED WITH MOTOR.
 - GROUND SCREW LOCATED IN OUTLET BOX.
 - ALL DIMENSIONS REFERENCE UNLESS OTHERWISE SPECIFIED BY OVER-UNDER DIMENSIONS.

<small>ITEMS AND MATERIALS SPECIFIED HEREIN MUST COMPLY WITH THE EUROPEAN REDUCTION OF HAZARDOUS SUBSTANCES (ROHS 3) DIRECTIVE, 2002/95/EC, REGULATIONS (EC) NO. 1907/2006 (REACH) AS OF 1 JUNE 2007, CALIFORNIA PROP 65 AND ALL SUBSEQUENT UPDATES. PLEASE REFER TO THE OFFICIAL DOCUMENTS FOR COMPLETE SPECIFICATIONS AND LIMITS FOR ALL RESTRICTED SUBSTANCES UNDER ROHS 3, REACH AND CALIFORNIA PROP 65.</small>		REVISION DESCRIPTION FOR: - - - - NEW		SCALE: 1:2 UNITS: INCHES		TITLE: DRAWING, DIMENSION		NIDEC MOTOR CORPORATION	
MATERIAL: - - - -		TOLERANCES ON DIMENSIONS (UNLESS OTHERWISE SPECIFIED): INCHES mm		ISSUED BY: D. CISNEROS APPROVED BY: E. LUNA		REVISION DATE: 30-SEP-20		SHEET NUMBER: 1 OF 1 DWG SIZE: C	
NIDEC CONFIDENTIAL <small>NIDEC MOTOR CORPORATION 30-SEP-20</small>		ANGLES X°= ±1°		T849		SOLIDEDGE			