



HVAC Motors

FAN and BLOWER MOTOR DIRECT DRIVE PSC
HEAVY GAUGE ROLLED STEEL CONSTRUCTION
 OPEN AIR OVER DESIGN FLEX MOUNT MOTORS

- Open Frames and Brackets
- Multi-speed Capacity
- Weather Resistant Reversing Plug
- 30" Long Leads
- Automatic Reset Thermal Protector
- Ball Bearings
- UL reconized and CSA Certified
- Capacitor Included
- Shaft 1/2" X 6"

MaxMotion



| HP | RPM | VOLTS | FRAME | CAT NO | F.L. AMPS | WT (LBS) | C DIMENSION (INCH) |
|-----|--------|-------|-------|------------|-----------|----------|--------------------|
| 1/3 | 1075/4 | 115 | 48Y | MDD136/4SP | 15 | 14 | 4.5 |
| 1/2 | 1075/4 | 115 | 48Y | MDD126/4SP | 18 | 18 | 5 |



Nidec
All for dreams

| HP | RPM | VOLTS | FRAME | CAT NO | F.L. AMPS | WT (LBS) | C DIMENSION (INCH) |
|-----|--------|-------------|-------|------------|-----------|----------|--------------------|
| 1/4 | 1800 | 115/230 | 48 | D14CPA2P49 | 3.1/1.5 | 18 | 9.9 |
| 1/3 | 1800 | 115/230 | 48 | D13CPA2P49 | 3.8/1.9 | 18 | 9.9 |
| 1/2 | 1800 | 115/230 | 56H | D12CPA2PH9 | 5.0/2.6 | 15 | 11.3 |
| 3/4 | 1800 | 115/230 | 56H | D34CPA2PH9 | 7.3/3.5 | 29 | 12.3 |
| 1 | 1800 | 115/230 | 56H | D1CPA2PH9 | 8.8/4.4 | 31 | 12.3 |
| 1.5 | 1800 | 115/230 | 56H | D32CPA2PH9 | 13.4/6.7 | 41 | 12.3 |
| 1/4 | 1725 | 115 | 48 | 8000 | 5.3 | 13 | 8.9 |
| 1/3 | 1725 | 115 | 48 | 8100 | 6.4 | 18 | 9.4 |
| 1/2 | 1725 | 115 | 48 | 8200 | 8.0 | 18 | 10.0 |
| 1/3 | 1000/4 | 115 | 48Y | 9377 | 6.0 | 18 | 9.8 |
| 1.5 | 1140 | 208-230/460 | 56Z | 1819H | 5.4/2.7 | 35 | 15.8 |
| 1.5 | 1140 | 575 | 56YZ | 4934 | 2.3 | 39 | 16.3 |
| 2 | 1140 | 575 | 56YZ | 1184 | 2.8 | 40 | 16.8 |
| 1 | 850 | 575 | 56Z | 1829H | 1.7 | 41 | 16.8 |



HVAC Motors



marathon™
Motors

| HP | RPM | VOLTS | FRAME | CAT NO | F.L. AMPS | WT (LBS) | C DIMENSION (INCH) |
|-----|--------|-------------|-------|--------------|--------------|----------|--------------------|
| 1/4 | 1725 | 115/208-230 | 48YZ | B313 | 5.2/2.8-2.6 | 16 | 9.95 |
| 1/3 | 1725 | 115/208-230 | 48YZ | B315 | 5.8/3.1-2.9 | 17 | 10.22 |
| 1/2 | 1725 | 115/208-230 | 56 | B317 | 8.0/4.1-4.0 | 20 | 10.32 |
| 3/4 | 1725 | 115/208-230 | 56 | B319 | 10.0/5.2-5.0 | 23 | 10.72 |
| 1 | 1725 | 115/208-230 | 56Z | 4688 | 14.4/7.2-7.4 | 28 | 11.75 |
| 1.5 | 1725 | 115/208-230 | 56H | C1160 | 16.4/8.4-8.2 | 35 | 11.91 |
| 1/4 | 1725 | 115 | 48YZ | B206 | 5.0 | 14 | 9.62 |
| 1/3 | 1725 | 115 | 48YZ | B207 | 5.5 | 15 | 9.62 |
| 1/2 | 1725 | 115 | 48YZ | B208 | 7.5 | 20 | 10.43 |
| 1/3 | 1075/4 | 115 | 48Y | X035 | 4.5 | 15 | 4.50 |
| 1.5 | 1140 | 200-230/460 | 56Y | X503 | 5.5-5.4/2.7 | 35 | 11.00 |
| 1.5 | 1140 | 575 | 56Y | X524 | 2.2 | 35 | 11.00 |
| 2 | 1140 | 575 | 56Y | X526 | 2.7 | 45 | 11.63 |
| 1 | 850 | 575 | 56Y | X527 | 2.1 | 46 | 12.00 |



ROTOM

| HP | RPM | VOLTS | FRAME | CAT NO | AMPS | WT (LBS) | BODY LENGTH |
|-----|--------|---------|-------|---------------|------|----------|-------------|
| 1/3 | 1075/4 | 115 | 48Y | DD-035 | 4.80 | 15 | 4.30 |
| 1/2 | 1075/4 | 115 | 48Y | DD-036 | 7.6 | 15 | 4.85 |
| 1/4 | 1075/4 | 208-230 | 48Y | DD-044 | 1.9 | 14 | 4.0 |
| 1/3 | 1075/4 | 208-230 | 48Y | DD-045 | 1.75 | 13 | 4.37 |
| 1/2 | 1075/4 | 208-230 | 48Y | DD-046 | 3.3 | 15 | 4.79 |