

PERFORMANCE DATA SHEET NEMA PREMIUM NR CAN NEMA 12 - 12

Catalogue #: **MPP-63**

HP	kW	Voltage	S.F. @ 60Hz	EFF.	P.F.	Frame	Design	L.R. Amps
50	37,30	575	1,25	94,1%	0,79	365T	B	290

60 Hz								
FLA							Code	F.L. RPM
208	230	416	460	480	575	600		
/	/	/	/	/	50	/	G	1187

50 Hz							
FLA			S.F. @ 50Hz	Efficiency	Power Factor	Code	F.L. RPM
190	380	415					
/	/	/	/	/	/	/	/


Wgt. Lbs	PH	Duty	Insul. Class	Amb.	Elevation	Temp. Rise° C
752	3	Cont.	F	40°C	1000M (3300 Ft)	< 80

% Efficiency		% Power Factor		Torque		Winding Resist. Ω	Safe Cold Start (Secs)
Full Load:	94,1%	Full Load:	0,79	Full Load Ft/Lbs	221,2		
3/4 Load:	94,2%	3/4 Load:	0,76	Locked Rotor %	150		
1/2 Load:	93,8%	1/2 Load:	0,67	Break Down %	260		

Rotor Inertia Wk2 Lb-Ft2	Max Load Inertia Wk2 Lb-Ft2	Shaft Material	Frame Material	DE Bracket Type	ODE Bracket Type	Enclosure	NEMA Rating	Lead Wire Size
14,95	846,3	Standard	Cast Iron	Standard	Standard	TEFC	IP55	8AWG

Ball Bearings		Grease	Mount Type	Orientation	Paint	Sound Pressure @ 3FT	Sound Power
DE	ODE						
6313	6313	Mobil PolyrexEm	Rigid	Horizontal	Green	75	86

Inverter Duty. Motor meets MG1 parts 31.4.4.2	Constant Torque Range	Variable Torque Range	Constant HP RPM
		10:1	20:1




Date: 2020-02-27
 Customer: _____
 Contact: _____
 Submittee: J.C. Lavallée


Catalogue #: MPP-63

NEMA PREMIUM NR CAN NEMA 12 - 12										
HP	VAC	RPM	Enclosure	Frame	Frequency	Design	Poles	LR Code Letter	Insulation Class	Temp. Rise °C
50	575	1187	TEFC	365T	60	B	6	G	F	< 80
	0Hz	6Hz	15Hz	30Hz	45Hz	60Hz	75Hz	90Hz	105Hz	120Hz
Amps	50	50	50	50	50	50	50	50	50	50
RPM	0	118,7	296,75	593,5	890,25	1187	1483,75	1780,5	2077,25	2374
Torq ft.lb	176,98	221,23	221,23	221,23	221,23	221,23	176,98	147,49	126,42	110,61
Peak Tq ft.lb	254,41	508,83	508,83	508,83	508,83	508,83	407,06	339,22	290,76	254,41
HP	0	5,0	12,5	25,0	37,5	50,0	50,0	50,0	50,0	50,0
	Locked Rotor	Pull-Up	Breakdown	Rated Load	Idle	Duty	S. F.	Ambient	Elevation	dBA @ 1M
Speed (RPM)	0,0	504	960	1187	1200	Continuous	1,25	40°C	3300 ft	75
Current (Amps)	290,0	246,5	172,6	50,0	19,4	VFD Rating: Meets MG1 parts 31.4.4.2				
Torque (ft-lbs)	331,8	248,9	575,2	221,2	0,0	C.T.	10:1	V.T.	20:1	

Motor Speed Data



Motor Torque Capability vs RPM





Date: 2020-02-27
 Customer: _____
 Contact: _____
 Submittee: J.C. Lavallée

Catalogue #: **MPP-63**

NEMA PREMIUM NR CAN NEMA 12 - 12										
HP	VAC	RPM	Enclosure	Frame	Frequency	Design	Poles	LR Code Letter	Insulation Class	Temp. Rise °C
50	575	1187	TEFC	365T	60	B	6	G	F	< 80
Load %	0%	25%	50%	75%	100%	125%	150%			
Amps	19,35	21,50	30,10	40,30	50,00	57,18	69,66			
Torq ft/lbs	0	54,86	110,01	165,47	221,23	277,30	333,67			
RPM	0	1196,75	1193,5	1190,25	1187	1183,75	1180,5			
Eff	0	81,71	93,80	94,20	94,10	94,10	94,10			
PF	0	53,3	67	76	79	87	85,7			
	Locked Rotor	Pull-Up	Breakdown	Rated Load	Idle	Duty	S. F.	Ambient	Elevation	dBA @ 1M
Speed (RPM)	0	504	960	1187	1200	Continuous	1,25	40°C	3300 ft	75
Current (Amps)	290	246,5	172,6	50	19,35	VFD Rating: Meets MG1 parts 31.4.4.2				
Torque (ft-lbs)	331,84	248,88	575,20	221,23	0,0	C.T.	10:1	V.T.	20:1	

