



**PERFORMANCE DATA SHEET
NEMA PREMIUM NR CAN NEMA 12 - 12**

Catalogue #: **MQOP-66**

HP	kW	Voltage	S.F. @ 60Hz	EFF.	P.F.	Frame	Design	L.R. Amps
60	44,76	230/460	1,15	93,6%	0,91	364TS	B	435

60 Hz							Code	F.L. RPM
208	230	416	460	480	575	600		
/	132	/	66,00	/	/		G	3550

50 Hz								
FLA			S.F. @ 50Hz		Efficiency	Power Factor	Code	F.L. RPM
190	380	415						
160,0	80		1,00		92,0%	0,930	D	2960

Wgt. Lbs	PH	Duty	Insul. Class	Amb.	Elevation	Temp. Rise° C
704	3	Cont.	F	40°C	1000M (3,300 Ft)	< 80

% Efficiency		% Power Factor		Torque		Winding Resist. Ω	Safe Cold Start (Secs)
Full Load:	93,6%	Full Load:	0,91	Full Load Ft/Lbs	88,8		
3/4 Load:	93,0%	3/4 Load:	0,89	Locked Rotor %	170		
1/2 Load:	92,4%	1/2 Load:	0,84	Break Down %	255	0	20

Rotor Inertia Wk2 Lb-Ft2	Max Load Inertia Wk2 Lb-Ft2	Shaft Material	Frame Material	DE Bracket Type	ODE Bracket Type	Enclosure	NEMA Rating	Lead Wire Size
6,17	80	1045	Cast Iron	Cast Iron	Cast Iron	ODP	IP23	7AWG

Ball Bearings		Grease	Mount Type	Orientation	Paint	Sound Pressure @ 3FT	Sound Power
DE	ODE						
6313	6313	Mobil PolyrexEm	Rigid	Horizontal	RAL6022	90	101



Inverter Duty, Motor meets MG1 parts 31.4.4.2	VFD SF	Constant Torque Range	Variable Torque Range	Constant HP RPM
	1,00	10:1	20:1	5400



Date: 2023-12-13
 Customer: _____
 Contact: _____
 Submittee: J.C. Lavallée

Catalogue #: MQOP-66

NEMA PREMIUM NR CAN NEMA 12 - 12										
HP	VAC	RPM	Enclosure	Frame	Frequency	Design	Poles	LR Code Letter	Insulation Class	Temp. Rise °C
60	460	3550	ODP	364TS	60 Hz	B	2	G	F	< 80
	0Hz	6Hz	15Hz	30Hz	45Hz	60 Hz	75Hz	90Hz	105Hz	120Hz
Amps	66	66	66	66	66	66	66	66	66	66
RPM	0	355	887,5	1775	2662,5	3550	4437,5	5325	6212,5	7100
Torq ft.lb	71,01	71,01	88,77	88,77	88,77	88,77	71,01	59,18	50,72	44,38
Peak Tq ft.lb	100,97	201,94	201,94	201,94	201,94	201,94	161,55	134,63	115,40	100,97
HP	0	4,8	15,0	30,0	45,0	60,0	60,0	60,0	60,0	60,0
	Locked Rotor	Pull-Up	Breakdown	Rated Load	Idle	Duty	S. F.	Ambient	Elevation	dBA @ 1M
Speed (RPM)	0,0	1512	2880	3550	3600	Continuous	1,15	40°C	3,300 ft	90
Current (Amps)	435,0	369,8	258,8	66,0	25,1	VFD Rating: Meets MG1 parts 31.4.4.2				
Torque (ft.-lbs)	150,9	113,2	226,4	88,8	0,0	C.T.	10:1	V.T.	20:1	VFD SF 1.00




Date: 2023-12-13
 Customer:
 Contact:
 Submittee: J.C. Lavallée

Catalogue #: MQOP-66

NEMA PREMIUM NR CAN NEMA 12 - 12										
HP	VAC	RPM	Enclosure	Frame	Frequency	Design	Poles	LR Code Letter	Insulation Class	Temp. Rise °C
60	460	3550	ODP	364TS	60 Hz	B	2	G	F	< 80
Load %	0%	25%	50%	75%	100%	125%	150%			
Amps	25,08	23,60	39,07	51,55	66,00	82,93	101,93			
Torq ft/lbs	0	21,96	44,07	66,34	88,77	111,35	134,09			
RPM	0	3587,5	3575	3562,5	3550	3537,5	3525			
Eff	0	85,16	92,40	93,00	93,60	92,13	91,77			
PF	0	69,9	84	89	91	91,91	90,09			
Speed (RPM)	Locked Rotor	Pull-Up	Breakdown	Rated Load	Idle	Duty	S. F.	Ambient	Elevation	dBA @ 1M
0	0	1512	2880	3550	3600	Continuous	1,15	40°C	3,300 ft	90
Current (Amps)	435	369,8	258,8	66	25,08	VFD Rating: Meets MG1 parts 31.4.4.2				
Torque (ft-lbs)	150,90	113,18	226,35	88,77	0,0	C.T.	10:1	V.T.	20:1	VFD SF 1.00

Motor Speed Data



Motor Load Data

