



Date: 2020-04-13

Description								
VFD-B, 15/20HP, 11/15Kw, CT/VT, 24/30A, 3 Ø 460VAC, 2000Hz, (V/Hz, SVC, VC+PG), NEMA 1, Frame C								
Manufacturer	Heavy Duty Output Rating		Normal Duty Output Rating		Light Duty Output Rating		Single Phase Duty Rating	
Delta Electronics	HD Input Amps Rating	24,7	ND Input Amps Rating	-	LD Input Amps Rating	29,7	1 Ø Input Amps Rating	24,7
	Rated HP	Rated Amps	HP	Rated Amps	HP	Rated Amps	HP	Amps
	15,0	24,0	-	-	-	-	7,5	12,0
	Max. HP	Max. Amps	Max. HP	Max. Amps	Max. HP	Max. Amps	Max. HP	Max. Amps
Max. Capacity	20,0	28,8	-	-	20,0	28,8	7,5	12,0
Line Reactor	Heavy Duty		Normal Duty		Light Duty		1 Ø Phase	
	Line	Load	Line	Load	Line	Load	Line	Load
Model	KDRB2H	KDRB2L	-	-	KDRC3H	KDRB1L	KDRB2H	KDRAA4L2
HP Rating	15,0	15,00	-	-	20,00	20,00	15,00	7,50
Max Amps	27,0	30,0	-	-	27,0	30,0	27,0	11,0
Inductance uH	1690	912	-	-	1210	694	1690	1680
Nema 1 Encl.Size	C1	C1	-	-	C1	C1	C1	C1
Motor Models Compatible	Heavy Duty		Normal Duty		Light Duty		1 Ø Phase	
	Model	HP	Model	HP	Model	HP	Model	HP
	MQP-43	20	-	-	MQP-43	20	MQP-28	7,5
	FLA	25	FLA	-	FLA	25,0	FLA	9,8
VFD Dimensions	Width (mm)	Width (in.)	Height (mm)	Height (in.)	Depth (mm)	Depth (in)	Wgt (Kg)	Wgt (lbs)
	200	7,874	323	12,71651	183,2	7,212584	13,0	30,1665
	Input Voltage	Input Frequency	Input Phase	Enclosure	Control Method	V/Hz, Sensorless Vector, Closed Loop Vector		
	380 ~ 480VAC (± 10%)	50/60Hz (±5%)	3	NEMA 1				
Regulated Output Voltage	Efficiency	Motor Current Protection Range	Stall Prevention Level HD	Stall Prevention Level ND	Stall Prevention Level LD	Carrier Frequency	Accel / Decel Time	Default Rating
0.1 ~ 510.0Vac	≥97%	7.2 ~ 28.8 A	20 ~ 250%	-	-	1 ~ 15kHz	0.1 ~ 3600 secs	Heavy Duty
Over Torque Level	DC Injection	Braking Chopper	Equivalent Braking Resistor Circuit	Minimum Braking Resistance Value	Starting Torque @			
					V/Hz	SVC	VC+PG	
10 ~ 200%	0 ~ 100.0 %	Built-in	1000W 50Ω	39 Ω	10 ~ 200% @ 1.0Hz	10 ~ 200% @ 0.5Hz	10 ~ 200% @ 0.2Hz	
Analog Inputs			Analog Outputs			Keypad	Fault Record	Reel Time Stamp
AVI	ACI	AUI	AFM1	AFM2	DFM			
0 ~ 10vdc	0/4 ~ 20ma	-10 ~ +10vdc	0 ~ 10vdc	-	Pulsed Frequency	Removable	4 last faults	No
Digital Inputs					Signal mode			
Dedicated		Safe Torque Off	Programmable	Control Voltage				
Fwd, Rev, External Fault, Jog, Trg		No	6	24vdc	Sink (NPN) / Source (PNP)			
Digital Outputs				Built in Controllers				
DO1	DO2	DO3	DO4	Preset speeds	Process Control	PLC	PID	Position
1NO/NC Form C relay, ≤ 240VAC, ≤ 24vdc	Optocoupler NPN ≤ 48vdc	Optocoupler NPN ≤ 48vdc	Optocoupler NPN ≤ 48vdc	15	15 Steps	No	Yes	No
Communication				Built In Protocol 1	Built In Protocol 2	Built In Protocol 3		
Comm Port 1	Comm Port 2	Comm port 3	Comm port 4					
RJ-11 (RS-485)	-	-	-	Modbus ACSII	Modbus RTU	-		
Options								
Option 1	VFD-PU06	Upload / Download Keypad, Compatible with all Delta Series except, V, VE,MS/MH300, C2000 series, RJ11 Comm port connectable						
Option 2	RPA-01	Recessed Keypad Holder for remote location mounting of VFD-B Standard keypad (VFD-PU01)						
Option 3	VFD-PU01	VFD-B Standard Removable Keypad, Shipped with every B Series drive, NEMA 12						
Option 4	-	-						
Option 5	PG-02	VFD-B, V & VE Encoder Input Card, 12/5vdc output, Compatible with Output Voltage, Open Collector, Line Driver & Complementary Encoders						
Option 6	PG-03	VFD-B Encoder Input Card, 12vdc output, Compatible with Output Voltage, Open Collector, Line Driver & Complementary Encoders						
Option 7	RC-01	Remote Station, NEMA 1, Rev/Fwd, Run/Stop, Jog/Reset, Potentiometer, & Analog Frequency Display, compatible with all VFD series						
Option 8	DN-02	DeviceNet Communication module, compatible with VFD-B, M, & S series						
Option 9	PD-01	ProfiBus Communication module, compatible with VFD-B, M, & S series						
Option 10	LN-01	LonWorks Communication module, compatible with VFD-B, M, & S series						
Option 11	EG1010A	1 meter Extension Cable for remote Keypad mounting, compatible with B, M, E, MH-300 & MS-300 series removable Keypads						
Option 12	EG2010A	2 meter Extension Cable for remote Keypad mounting, compatible with B, M, E, MH-300 & MS-300 series removable Keypads						
Option 13	EG3010A	3 meter Extension Cable for remote Keypad mounting, compatible with B, M, E, MH-300 & MS-300 series removable Keypads						
Option 14	EG5010A	5 meter Extension Cable for remote Keypad mounting, compatible with B, M, E, MH-300 & MS-300 series removable Keypads						
Option 15	-	-						
Option 16	-	-						
Option 17	-	-						
Option 18	-	-						