



Model #: **VFD2000C63B-00**

Date: 2020-04-14

Description								
VFD-C2000, 175/250HP, 130/186.5Kw, (HD 162/LD 264A), 3 Ø 690VAC, 599.0Hz, (V/Hz, VC+PG, SVC, FOC, TQC & PM), c/w PLC, IP20, Frame F								
Manufacturer	Heavy Duty Output Rating		Normal Duty Output Rating		Light Duty Output Rating		Single Phase Duty Rating	
Delta Electronics	HD Input Amps Rating	183,7	ND Input Amps Rating	220,4	LD Input Amps Rating	269,4	1 Ø Input Amps Rating	183,7
	Rated HP	Rated Amps	HP	Rated Amps	HP	Rated Amps	HP	Amps
	150,0	150,0	150,0	180,0	250,0	220,0	75,0	75,0
	Max. HP	Max. Amps	Max. HP	Max. Amps	Max. HP	Max. Amps	Max. HP	Max. Amps
Max. Capacity	200,0	180,0	200,0	216,0	250,0	264,0	75,0	75,0
Line Reactor	Heavy Duty		Normal Duty		Light Duty		1 Ø Phase	
	Line	Load	Line	Load	Line	Load	Line	Load
Model	KDRG45H	KDRI42L	KDRJ41H	KDRI42L	KDRL46H	KDRG47L	KDRG45H	KDRF45L
HP Rating	150,0	200,00	200,0	200,00	250,00	250,00	150,00	100,00
Max Amps	155,0	192,0	192,0	192,0	260,0	242,0	155,0	99,0
Inductance uH	326	146	250,0	146	188	108	326	272
Nema 1 Encl.Size	C4	C4	C5	C4	C5	C4	C4	C4
Motor Models Compatible	Heavy Duty		Normal Duty		Light Duty		1 Ø Phase	
	Model	HP	Model	HP	Model	HP	Model	HP
	MPP-97	200	MPOP-98	200	MPOP-102	250	MPP-78	100
	FLA	176	FLA	185,0	FLA	224,0	FLA	96
VFD Dimensions	Width (mm)	Width (in.)	Height (mm)	Height (in.)	Depth (mm)	Depth (in)	Wgt (Kg)	Wgt (lbs)
	420	16,5354	800	31,496	300	11,811	88,0	204,204
Regulated Output Voltage	Input Voltage	Input Frequency	Input Phase	Enclosure	Control Method	V/Hz, Sensorless Vector, Closed Loop Vector, FOC (Field Oriented Control), Torque Control, PM Motor Control		
	470 ~ 690VAC (± 10%)	50/60Hz (±5%)	3	NEMA 1 Optional				
Over Torque Level	Efficiency	Motor Current Protection Range	Stall Prevention Level HD	Stall Prevention Level ND	Stall Prevention Level LD	Carrier Frequency	Accel / Decel Time	Default Rating
	0.0 ~ 720.0Vac	≥98%	26.4 ~ 264.0 A	0 ~ 180%	0 ~ 150%	0 ~ 120%	2 ~ 9kHz	0.0 ~ 6000 secs
Analog Inputs	DC Injection	Braking Chopper	Equivalent Braking Resistor Circuit	Minimum Braking Resistance Value	Starting Torque @			
	10 ~ 250%	0 ~ 100.0 %	1 X VFD6200	18000W 9Ω	6.9 Ω	0 ~ 250% @ 0.5Hz	0 ~ 250% @ 0.5Hz	0 ~ 250% @ 0.0Hz
AVI	ACI	AUI	AFM1	AFM2	DFM	Keypad	Fault Record	Reel Time Stamp
0 ~ 10vdc	0/4 ~ 20ma	-10 ~ +10vdc	0 ~ 10vdc / 0 ~20ma	0 ~ 10vdc / 0 ~20ma	Pulsed Frequency			
Digital Inputs					Signal mode			
Dedicated	Safe Torque Off	Programmable	Control Voltage	Sink (NPN) / Source (PNP)				
Fwd, Rev, STO1, STO2	Yes	8	24vdc					
Digital Outputs				Built in Controllers				
DO1	DO2	DO3	DO4	Preset speeds	Process Control	PLC	PID	Position
1NO/NC Form C relay, ≤ 240VAC, ≤ 24vdc	1NO/NC Form C relay, ≤ 240VAC, ≤ 24vdc	Optocoupler NPN ≤ 48vdc	Optocoupler NPN ≤ 48vdc	15	Thru PLC	10K Steps	Yes	Yes
Communication				Built In Protocol 1	Built In Protocol 2	Built In Protocol 3		
Comm Port 1	Comm Port 2	Comm port 3	Comm port 4	Modbus ACSII	Modbus RTU	-		
RJ45 (RS-485)	RJ45 (RS-485)	-SG, +SG (RS-485)	-					
Options								
Option 1	KPC-CC01	Standard keypad shipped with C2000 series. Also compatible, MS-300 & MH-300.						
Option 2	MKC-KPPK	VFD-C2000, Keypad Remote Panel Adapter, IP66						
Option 3	KPC-CE01	VFD-C2000, LED English Keypad for C2000						
Option 4	CMC-EC01	VFD-C2000, EtherCAT Communication card, supports EtherCAT protocol						
Option 5	CMC-EIP01	VFD-C2000, Ethernet Communication card, supports EtherNet/IP protocol						
Option 6	CMC-MOD01	VFD-C2000, Ethernet communication card, supports MODBUS TCP protocol						
Option 7	CMC-DN01	VFD-C2000, DeviceNet communication card, 125kbps / 250kbps / 500kbps						
Option 8	CMC-PD01	VFD-C2000, PROFIBUS-DP communication card, 9.6kbps-12Mbps						
Option 9	EMC-COP01	VFD-C2000, CANopen communication card, 50kbps - 1Mbps						
Option 10	EMC-D42A	VFD-C2000, IO Extension card, (4DI/2DO), DC 24V						
Option 11	EMC-D611A	VFD-C2000, 6DI extension card, AC 110V power						
Option 12	EMC-BPS01	VFD-C2000, 24VDC External Power Supply Card						
Option 13	EMC-PG01L	VFD-C2000, Encoder Interface card, 5 VDC to encoder, Line-drive 300k pulse/sec. 5VDC 50mA pulse output						
Option 14	EMC-PG01O	VFD-C2000, Encoder Interface card, 5 or 12 VDC to encoder, Open-collect 300k pulse/sec. pulse output						
Option 15	EMC-PG01R	VFD-C2000, Resolver Feedback Card; VFD-C, CP						
Option 16	EMC-PG01U	VFD-C2000, Encoder Interface card, 5 VDC to encoder, Line-drive (A,B,Z,U,V,W) . 5VDC 50mA pulse output						
Option 17	EMC-R6AA	VFD-C2000, IO Extension card (6 output relays)						
Option 18	MKC-FN1CB	VFD-C2000, Conduit Box Kit, Frame F, NEMA 1						