



Date: 2020-04-15

Description								
VFD-MS300, 15/20HP, 11/15kw, (HD 45.9/ND 61.2A), 3 Ø 230VAC, 599.0Hz, (V/Hz, SVC, PM), IP20, Frame E1								
Manufacturer	Heavy Duty Output Rating		Normal Duty Output Rating		Light Duty Output Rating		Single Phase Duty Rating	
Delta Electronics	HD Input Amps Rating	58,8	ND Input Amps Rating	61,2	LD Input Amps Rating	-	1 Ø Input Amps Rating	61,2
	Rated HP	Rated Amps	HP	Rated Amps	HP	Rated Amps	HP	Amps
	15,0	49,0	15,0	51,0	-	-	7,5	24,5
	Max. HP	Max. Amps	Max. HP	Max. Amps	Max. HP	Max. Amps	Max. HP	Max. Amps
Max. Capacity	20,0	58,8	20,0	61,2	-	-	7,5	24,5
Line Reactor	Heavy Duty		Normal Duty		Light Duty		1 Ø Phase	
	Line	Load	Line	Load	Line	Load	Line	Load
Model	KDRD22H	KDRD24L	KDRC22H	KDRD26L	-	-	KDRD22H	KDRB23L
HP Rating	15,0	15,00	20,0	20,00	0,00	-	15,00	7,50
Max Amps	47,0	48,0	62,0	62,0	-	-	47,0	25,0
Inductance uH	375	220	278,0	172	-	-	375	434
Nema 1 Encl.Size	C2	C2	C2	C2	-	-	C2	C2
Motor Models Compatible	Heavy Duty		Normal Duty		Light Duty		1 Ø Phase	
	Model	HP	Model	HP	Model	HP	Model	HP
	MQP-37	15	MQP-43	20	-	-	MQP-28	7.5
	FLA	36,4	FLA	50,0	FLA	-	FLA	19,6
VFD Dimensions	Width (mm)	Width (in.)	Height (mm)	Height (in.)	Depth (mm)	Depth (in)	Wgt (Kg)	Wgt (lbs)
	130	5,1181	250	9,8425	185	7,28345	4,0	9,212385
	Input Voltage	Input Frequency	Input Phase	Enclosure	Control Method	V/Hz, Sensorless Vector, PM Motor Control		
	200 ~ 240VAC (± 10%)	50/60Hz (±5%)	3	NEMA1 Optional				
Regulated Output Voltage	Efficiency	Motor Current Protection Range	Stall Prevention Level HD	Stall Prevention Level ND	Stall Prevention Level LD	Carrier Frequency	Accel / Decel Time	Default Rating
0.0 ~ 255.0Vac	≥97%	4.90 ~ 61.20 A	0 ~ 200%	0 ~ 150%	-	2 ~ 15kHz	0.00 ~ 600.00	Heavy Duty
Over Torque Level	DC Injection	Braking Chopper	Equivalent Braking Resistor Circuit	Minimum Braking Resistance Value	Starting Torque @			
					V/Hz	SVC	VC+PG	
10 ~ 250%	0 ~ 100.0 %	Builitn	1500W 13Ω	12.6 Ω	10 ~ 200% @ 3.0Hz	10 ~ 200% @ 0.3Hz	-	
Analog Inputs			Analog Outputs			Keypad	Fault Record	Reel Time Stamp
AVI	ACI	AUI	AFM1	AFM2	DFM			
0 ~ 10vdc or -10 ~ +10vdc	0/4 ~ 20ma or 0 ~ 10vdc	-	0/4 ~ 20ma or 0 ~ 10vdc	-	-	Removable	10 last faults	Thru PLC
Digital Inputs					Signal mode			
Dedicated		Safe Torque Off	Programmable	Control Voltage				
STO1, STO2		Yes	7	24vdc	Sink (NPN) / Source (PNP)			
Digital Outputs				Built in Controllers				
DO1	DO2	DO3	DO4	Preset speeds	Process Control	PLC	PID	Position
1NO/NC Form C relay, ≤ 240VAC, ≤ 24vdc	Optocoupler NPN ≤ 48vdc	Optocoupler NPN ≤ 48vdc	-	15	No	2K Steps	Yes	No
Communication				Built In Protocol 1	Built In Protocol 2	Built In Protocol 3		
Comm Port 1	Comm Port 2	Comm port 3	Comm port 4					
USB type B	RJ45 (RS-485) / SG+, SG-	-	-	Modbus ACSII	Modbus RTU	-		
Options								
Option 1	KPC-CC01	Standard keypad shipped with C2000 series. Also compatible, MS-300 & MH-300.						
Option 2	MKC-KPPK	VFD-C2000, Keypad Remote Panel Adapter, IP66						
Option 3	MKM-EPE	VFD-MH/MS300, EMC Shielded Cable Earthing Plate, Frame E						
Option 4	-	-						
Option 5	KPC-CE01	VFD-C2000, LED English Keypad for C2000						
Option 6	MKM-CBE	VFD-MH/MS300, NEMA1 conduit box frame E						
Option 7	CMM-COP01	VFD-MH/MS300, CANopen Communication Card						
Option 8	CMM-DN01	VFD-MH/MS300, DeviceNet Communication Card						
Option 9	CMM-EIP01	VFD-MH/MS300, EtherNet/IP Communication Card						
Option 10	CMM-EC01	VFD-MH300, EtherCAT Communication Card						
Option 11	CMM-MOD01	VFD-MH/MS300, Modbus TCP Communication Card						
Option 12	CMM-PD01	VFD-MH/MS300, Profibus DP Communication Card						
Option 13	EMM-BPS01	VFD-MH/MS300, Back-up Power Supply card						
Option 14	-	-						
Option 15	EG1010A	1 meter Extension Cable for remote Keypad mounting, compatible with B, M, E, MH-300 & MS-300 series removable Keypads						
Option 16	EG2010A	2 meter Extension Cable for remote Keypad mounting, compatible with B, M, E, MH-300 & MS-300 series removable Keypads						
Option 17	EG3010A	3 meter Extension Cable for remote Keypad mounting, compatible with B, M, E, MH-300 & MS-300 series removable Keypads						
Option 18	EG5010A	5 meter Extension Cable for remote Keypad mounting, compatible with B, M, E, MH-300 & MS-300 series removable Keypads						