



Model #: VFD7A5MS21MNSAA

Date: 2020-04-15

Description								
VFD-MS300, 2/3HP, 1.5/2.2kw, (HD 7.65/ND 10.2A), 1 Ø 230VAC, 599.0Hz, (V/Hz, SVC, PM), IP66, Frame A2								
Manufacturer	Heavy Duty Output Rating		Normal Duty Output Rating		Light Duty Output Rating		Single Phase Duty Rating	
Delta Electronics	HD Input Amps Rating	-	ND Input Amps Rating	-	LD Input Amps Rating	-	1 Ø Input Amps Rating	15,8
	Rated HP	Rated Amps	HP	Rated Amps	HP	Rated Amps	HP	Amps
	-	-	-	-	-	-	2,0	10,2
	Max. HP	Max. Amps	Max. HP	Max. Amps	Max. HP	Max. Amps	Max. HP	Max. Amps
Max. Capacity	-	-	-	-	-	-	2,0	10,2
Line Reactor	Heavy Duty		Normal Duty		Light Duty		1 Ø Phase	
	Line	Load	Line	Load	Line	Load	Line	Load
Model	-	KDRMA27L1	-	KDRAA28L2	-	-	KDRB25H	KDRMA27L1
HP Rating	-	2,00	0,0	3,00	0,00	-	5,00	2,00
Max Amps	-	10,0	-	11,0	-	-	17,0	10,0
Inductance uH	-	1350	-	971	-	-	1030	1350
Nema 1 Encl.Size	-	C1	-	C1	-	-	C1	C1
Motor Models Compatible	Heavy Duty		Normal Duty		Light Duty		1 Ø Phase	
	Model	HP	Model	HP	Model	HP	Model	HP
	MQP-12	2	MQP-18	3	-	-	MQP-12	2
	FLA	6,2	FLA	8,4	FLA	-	FLA	6,2
VFD Dimensions	Width (mm)	Width (in.)	Height (mm)	Height (in.)	Depth (mm)	Depth (in)	Wgt (Kg)	Wgt (lbs)
	160	6,2992	230	9,0551	160	6,2992	1,2	2,87742
Input Voltage	Input Voltage	Input Frequency	Input Phase	Enclosure	Control Method	V/Hz, Sensorless Vector, PM Motor Control		
	200 ~ 240VAC (± 10%)	50/60Hz (±5%)	1	NEMA 4X / IP66				
Regulated Output Voltage	Efficiency	Motor Current Protection Range	Stall Prevention Level HD	Stall Prevention Level ND	Stall Prevention Level LD	Carrier Frequency	Accel / Decel Time	Default Rating
0.0 ~ 255.0Vac	≥97%	0.75 ~ 10.20 A	0 ~ 200%	0 ~ 150%	-	2 ~ 15kHz	0.00 ~ 600.00	Heavy Duty
Over Torque Level	DC Injection	Braking Chopper	Equivalent Braking Resistor Circuit	Minimum Braking Resistance Value	Starting Torque @			
10 ~ 250%	0 ~ 100.0 %	Built-in	200W 91Ω	47.5 Ω	V/Hz	SVC	VC+PG	
					10 ~ 200% @ 3.0Hz	10 ~ 200% @ 0.3Hz		
Analog Inputs			Analog Outputs			Keypad	Fault Record	Reel Time Stamp
AVI	ACI	AUI	AFM1	AFM2	DFM			
0 ~ 10vdc or 10 ~ +10vdc	0/4 ~ 20ma or 0 ~ 10vdc	-	0/4 ~ 20ma or 0 ~ 10vdc	-	-	Not Removable	10 last faults	Thru PLC
Digital Inputs					Signal mode			
Dedicated		Safe Torque Off	Programmable	Control Voltage	Sink (NPN) / Source (PNP)			
STO1, STO2		Yes	7	24vdc				
Digital Outputs				Built in Controllers				
DO1	DO2	DO3	DO4	Preset speeds	Process Control	PLC	PID	Position
1NO/NC Form C relay, ≤ 240VAC, ≤ 24vdc	Optocoupler NPN ≤ 48vdc	Optocoupler NPN ≤ 48vdc	-	15	No	2K Steps	Yes	No
Communication				Built In Protocol 1	Built In Protocol 2	Built In Protocol 3		
Comm Port 1	Comm Port 2	Comm port 3	Comm port 4	Modbus ACSII	Modbus RTU	-		
USB type B	RJ45 (RS-485) / SG+, SG-	-	-					
Options								
Option 1	KPC-CC01	Standard keypad shipped with C2000 series. Also compatible, MS-300 & MH-300.						
Option 2	MKC-KPPK	VFD-C2000, Keypad Remote Panel Adapter, IP66						
Option 3	MKM-EPB	VFD-MH/MS300, EMC Shielded Cable Earthing Plate, Frame B						
Option 4	-							
Option 5	KPC-CE01	VFD-C2000, LED English Keypad for C2000						
Option 6	-							
Option 7	CMM-COP01	VFD-MH/MS300, CANopen Communication Card						
Option 8	CMM-DN01	VFD-MH/MS300, DeviceNet Communication Card						
Option 9	CMM-EIP01	VFD-MH/MS300, EtherNet/IP Communication Card						
Option 10	CMM-EC01	VFD-MH300, EtherCAT Communication Card						
Option 11	CMM-MOD01	VFD-MH/MS300, Modbus TCP Communication Card						
Option 12	CMM-PD01	VFD-MH/MS300, Profibus DP Communication Card						
Option 13	EMM-BPS01	VFD-MH/MS300, Back-up Power Supply card						
Option 14	-							
Option 15	-							
Option 16	-							
Option 17	-							
Option 18	-							